

Floton-1000

Floton pumps are mainly designed for dewatering applications during flood situations and removing water from basements and low lying areas. It is also useful for irrigation and to draw water from well lakes, ponds, well, river, etc for filling tankers and fire tenders. Owing to its high volume capacity it can also be used for emergency fire fighting applications. Since these pumps float on the water surface, common problems of suction with other pumps do not exist. The pump has the capability of dry run, so it can be started and then lowered in to a well without possibility of pump being seized.

Engine

- Model : B&S 4-stroke air cooled, petrol OHV
- Displacement / Power : 190 cc / 6 hp (approx)
- Bore x Stroke : 68 x 52 mm
- Air Cleaner/muffler : Water resistant
- Ignition System : Transistorized Magneto
- Fuel Tank Capacity : 1.2 Ltr.
- Starting System : Recoil

Pump

- Type : Single Suction, Centrifugal
- Casing : Aluminium - Anodized / Powder Coated
- Impeller : Aluminium - Anodized / Powder Coated
- Outlet : 63 mm instantaneous
- Performance : > 1000 l/min
- Delivery Height : >15 m
- Solids : Ø20 mm
- Min Water Depth : 20 mm of water

Dimensions and weight

- Dimensions (L x W x H) : 690 x 550 x 400 mm
- Weight : 30 kgs

Optionals:

- Fuel Tank 5 ltrs
- Remote On / Off
- LED Lights
- Fuel Indicator



Scan QR for Demo video

Manufactured By: